
















WizePanel - Interfaces (Adapters)

Adapter Name		Data Access	Source Definition & Filtering	Events	Placeholder Data Fields	Description
	CSV / MS Excel	file based (CSV) (file system, HTTP)	custom SOURCE UID string (e.g. Room1, Room2, ...) in a .csv file row	n events per 1 .csv file	<u>DTSTART</u> , <u>DTEND</u> , SUMMARY, DESCRIPTION, LOCATION + <i>custom data fields</i>	Reads events from custom .csv files via file system, SMB or HTTP.
	MS Exchange (EWS) / Outlook	mailbox calendar based (EWS) (HTTP)	mailbox calendar address	n events per 1 mailbox calendar	<u>DTSTART</u> , <u>DTEND</u> , SUMMARY, DESCRIPTION, LOCATION, CREATOR	Reads events from Microsoft Exchange mailbox calendars through MS EWS-API via HTTP.
	MS Exchange (Graph) / Outlook	mailbox calendar based (GRAPH) (HTTP)	mailbox calendar address	n events per 1 mailbox calendar	<u>DTSTART</u> , <u>DTEND</u> , SUMMARY, DESCRIPTION, LOCATION, CREATOR	Reads events from Microsoft Exchange mailbox calendars through MS Graph-API via HTTP.
	iCal / Google Calendar	data based (iCal) (HTTP)	URL to iCal data (Source: "EVENTS") ----- LOCATION attribute in .ics file (Source: [LOCATIONS])	n events per 1 URL	<u>DTSTART</u> , <u>DTEND</u> , SUMMARY, DESCRIPTION, LOCATION	Reads events in iCalendar format from Google Calendar or from custom URL via HTTP.
	iCal / ICS	folder based (iCal ICS) (file system)	LOCATION attribute in .ics file	n events per 1 .ics file n .ics files per 1 folder	<u>DTSTART</u> , <u>DTEND</u> , SUMMARY, DESCRIPTION, LOCATION	Reads events in iCalendar format from multiple .ics files in a custom folder via file system.
	XML	folder based (XML) (file system)	SOURCENAME attribute in .xml files	1 event per 1 .xml file n .xml files per 1 folder	<u>DTSTART</u> , <u>DTEND</u> , SOURCENAME, SUMMARY, DESCRIPTION, LOCATION + <i>custom data fields</i>	Reads events in XML format from multiple .xml files in a custom folder via file system.
	HTTP / JSON	data based (JSON) (HTTP)	target_name or name attribute in JSON string	stateless, no event handling custom data per 1 URL	DTSTART, DTEND, SUMMARY, DESCRIPTION, LOCATION + <i>custom data fields</i>	Reads custom data from an URL to a web server providing a special WizePanel JSON string via HTTP GET.
	WebUntis HTTP / JSON	room based (JSON) (HTTP)	room	n events per 1 room	<u>DTSTART</u> , <u>DTEND</u> , SUMMARY, DESCRIPTION, + <i>WebUntis specific data fields</i>	Reads events for rooms from an URL to WebUntis service as JSON string via HTTP.
	aSc TimeTables	data based (HTTP)	aSc timetable room	n events per 1 URL	<u>DTSTART</u> , <u>DTEND</u> , SUMMARY, ...	Reads events from an URL to an aSc timetable via HTTP.
	DEA Event Management System (EMS)	data based (EMS) (HTTP)	DEA-EMS room	n events per 1 URL	<u>DTSTART</u> , <u>DTEND</u> , SUMMARY, ...	Reads events for rooms from an URL to a DEA-EMS provided SOAP API via HTTP.
	Simple Events	manually added events (WizePanel-Studio > Events Tab)	predefined room in WizePanel-Studio	n events per 1 room	<u>DTSTART</u> , <u>DTEND</u> , SUMMARY	Allows users to manually create simple events in WizePanel-Studio > Events Tab on-the-fly.
	Energy Saver					Allows users to specify time periods for WizePanels to go into sleep mode and save energy.
	System Monitor					Enables basic WizePanel-System monitoring e-mail notifications via SMTP.